LENTA

Robustness and comfort

Dairy cattle

Robust and comfortable - for tying stalls and elevated feed stalls

In tying stalls and elevated feed stalls, robustness and comfort are two main challenges. The LENTA mat is specially designed for this application area and satisfies them both. The double-structured stud profile on the lower side provides pleasant softness and is extremely robust. Moreover, the actual weight of the mat ensures high dimensional stability. Dirt barriers on the lower side reduce soiling underneath the mat.
Incidentally: Elevated feed stalls also help to reduce ammonia emissions!



- **Proven, low maintenance pebbled surface**
- **Chamfer on the rear edge: protects joints, no stumbling edge**
- **Integrated slope to the rear edge helps keep the surface dry**
- **DIN class 1**

Technical data

Dimensions (mm / cm)	Thickness	Width	Length
LENTA	ca. 3 cm	110 cm	165 / 175 / 185 cm
		120 cm	150 / 157 / 165 / 175 / 185 / 200 cm
		130 cm	185 cm

Dimensions (in / ft)	Thickness	Width	Length
LENTA	ca. 1 ¼"	43 ¼"	65 / 68 ⅞ / 72 ⅞"

Dimensions (in / ft)	Thickness	Width	Length
		47 ¼"	59 / 61 ¾ / 65 / 68 ⅞ / 72 ⅞ / 78 ¾"
		51 ¼"	72 ⅞"

Optional accessories: KK connecting bar		Width	Length
Closure of gaps of up to 4 - 8 cm / 1 ⅝ - 3 ¼" in width	(e.g. with mushroom dividers or very fine bedding) or as a side closure	13 cm	165 / 180 cm
		5 ⅛"	65 / 71"

Installation and fixing

Mats are laid edge to edge.
Installation instructions

Fixing at the head edge Prefabricated fixing points facilitate installation.

Maintenance tip

When used as lying mats, add a thin layer of bedding, e.g. soft milled straw or mineral materials (moisture in the lying area can cause various conditions, including skin diseases and infections)

Keep mat as clean as possible in an elevated feed stall Essential for hoof health and slip resistance!

Treatment with a high-pressure cleaner and standard cleaning agents possible.

KRAIBURG warranty
10 years
Detailed information on our warranty (with consideration of the service life) is available upon request from your contractual partner / dealer.

Tolerances
Width + length: +/– 1.5% (DIN ISO 3302–1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.

***Note on imperial measurements:** Our products are manufactured according to metric specifications. The imperial measurements are therefore only intended as a guide. Inaccuracies may occur due to conversion and rounding.*

***Maintenance and usage instructions:** Our flooring for cattle husbandry has been tested under defined conditions for its slip resistance. However, the actual slip resistance in practical use depends on the relevant environmental and usage conditions. Especially moisture, dirt, mud, ice or snow, the slope, the condition of the ground and wear or damage can adversely affect performance characteristics. Individual factors such as health status, physical condition and exercise habits of the animals also affect slip resistance. Surfaces must therefore be checked regularly according to the relevant usage conditions, maintained and kept in proper condition. Further technical details on request.*

Gummiwerk KRAIBURG Elastik GmbH & Co. KG

Göllstraße 8 | 84529 Tittmoning, Germany | Phone: +49 8683 701-303 | E-mail: info@kraiburg-elastik.de
kraiburg-elastik.com