

The comfort deep bedded stall

maxiBOX is a special solution that combines the advantages of elevated stalls and deep bedded stalls. The 4-component system is installed on a ca. 10 cm high concrete surface and used with a ca. 3-5 cm layer of bedding. The maxiLONGLINE rubber flooring (roll) ensures a good basic level of softness, thereby creating year-round functional reliability with consistent comfort. Rubber brisket board and elastic rubber profile at the rear ensure added comfort when lying down. The integrated slope and drainage grooves in the rubber flooring as well as the drainage openings in the rear rubber bar allow liquids to drain away. Longitudinal profiles – installed on the rubber covering – serve as the lateral lying area boundary and reduce the slipping of bedding.



- U-shaped surface profiling is particularly good at keeping bedding in place
- Elastic closure front and rear
- Integrated slope and drainage grooves in the rubber flooring
- Drainage openings in the rear rubber bar
- Also available in XL lying length for more freedom when lying, lying down and getting up



Technical data

Dimensions (mm / cm)	Thickness / Height	Length	Width
maxiLONGLINE (rubber flooring)	ca. 3 cm	2.5 - 50 m in 10-cm increments	180 / 195 cm
			Special dimensions on request
maxiBOARD	11 cm	175 cm	13 cm

Dimensions (mm / cm)	Thickness / Height	Length	Width
maxiSTEP	12,5 cm	175 cm	12 cm
maxiPROFIL XL (lateral lying area boundary / closure of lateral edges / coverage of joints)	8 cm	173 cm	13 cm

Dimensions (in / ft)	Thickness / Height	Length	Width
maxiLONGLINE (rubber flooring)	ca. 1 ¼"	8 ½ - 164' in 4" increments	71 / 76 ¾"
			Special dimensions on request
maxiBOARD	4 ⅜"	68 ⅞"	5 ⅛"
maxiSTEP	5"	68 ⅞"	4 ¾"
maxiPROFIL XL (lateral lying area boundary / closure of lateral edges / coverage of joints)	3 ¼"	68 ⅞"	5 ⅛"

Note: Use a 4.5 cm high maxiPROFIL in Switzerland!

Concrete surface prerequisites

Min. 3% slope

Ca. 10 cm high

Installation and fixing

maxiLONGLINE is fixed to the concrete floor together with maxiBOARD.

[Installation instructions](#)

Fixing 7 fixings / maxiBOARD and maxiSTEP; 5 screws / maxiPROFIL XL

KRAIBURG warranty

10 years

(Only for exclusive use as a lying area, no combination, e. g. feeding + lying)

Detailed information on our warranty (with consideration of the service life) is available upon request from your contractual partner / dealer.

Tolerances

Width + length: +/- 1.5% (DIN ISO 3302-1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.

Note on imperial measurements: *Our products are manufactured according to metric specifications. The imperial measurements are therefore only intended as a guide. Inaccuracies may occur due to conversion and rounding.*