

Our softest mat - for the highest demands

The WINGFLEX wing profile is stable yet flexible and optimally adapts to the lying cow. The supporting studs provide the required firmness for punctual loads, such as when getting up and lying down. The soft lying area within the mat edges contribute to correct positioning of the cow and improves slip resistance. The integrated slope to the rear edge helps facilitate drainage of the surface, ensuring a drier lying area. The single mats are joined with connecting bars.



- Proven, low maintenance pebbled surface
- Chamfer on the rear edge: protects joints, no stumbling edge
- Excellent deformability and adaptation
- Suitable for suspended dividers and mushroom dividers
- Also available in XL lying length



Technical data

Dimensions (mm / cm)	Thickness	Width (can be controlled with connecting bar)	Length
WINGFLEX	ca. 6 cm	110 / 115 / 120 / 125 / 130 cm	183 cm
		120 / 125 / 130 cm	192 cm

Dimensions (in / ft)	Thickness	Width (can be controlled with connecting bar)	Length
WINGFLEX	ca. 2 ½"	43 ¾ / 45 ¼ / 47 ¼ / 49 ¼ / 51 ¼"	72"

Dairy cattle

Dimensions (in / ft)	Thickness	Width (can be controlled with connecting bar)	Length
		47 ¼ / 49 ¼ / 51 ¼"	75 ⅝"

Optional accessories: end bar	Width	Length
Side closure bar	6.3 cm / 2 ½"	183 cm / 72"

Optional accessories: Brisket boards

Elastic brisket board ergoBOARD
[Go to the product](#)

Robust brisket board maxiBOARD
[Go to the product](#)

Installation and fixing

The system is joined with bars. The widths of the bars vary to control the lying place width.
[Installation instructions](#)

Fixing at the head edge and bars Prefabricated fixing points facilitate installation.

Maintenance tip

Cover lying mats lightly with bedding e.g. soft milled straw or mineral materials (moisture in the lying area can cause various conditions, including skin diseases and infections)

Treatment with a high-pressure cleaner and standard cleaning agents possible.

KRAIBURG warranty

10 years

(Only for exclusive use as a lying area, no combination, e. g. feeding + lying)

Detailed information on our warranty (with consideration of the service life) is available upon request from your contractual partner / dealer.

Tolerances

Width + length: +/- 1.5% (DIN ISO 3302-1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.

Note on imperial measurements: Our products are manufactured according to metric specifications. The imperial measurements are therefore only intended as a guide. Inaccuracies may occur due to conversion and rounding.